

**Ducted Split System  
Air Conditioner**

**Technical Data**

**ISD 155K / OSA 155RKV**



**Optional  
SAT Controller**

**Single & Three Phase Versions**

**Extra Long Life  
Epoxy Coated Outdoor Coil**

**Nominal Cooling Capacity  
14.5 kW**

# ISD 155K / OSA 155RKV DUCTED SPLIT SYSTEM AIR CONDITIONER

## GENERAL

**OSA 155RKSV** – single phase version  
**OSA 155RKTV** – three phase version.

The ISD indoor unit, together with its associated OSA outdoor unit, provides a reverse cycle (heat pump) split system air conditioner designed and developed to comply with and exceed AS/NZS 3823 specified conditions (i.e. guaranteed cooling cycle performance at 43°C outdoor temperature).

## APPLICATIONS

These units have been specifically developed for air conditioning of light commercial and residential premises, e.g. offices, motels, shops and homes.

## Air Flow Selection

If the air returning to the indoor coil is regularly expected to be above 50%RH, then the coil face velocity should be limited to be 2.5 m/s or less (refer Air Flow graph; 2.5 m/s is clearly marked).

High humidity levels can occur in tropical or subtropical conditions, and/or when heavily moisture laden fresh air is introduced. Consideration must always be given to selecting an air flow and face velocity that avoids water carry-over problems.

Applications using full or high proportions of fresh air should be referred to your nearest **temperzone** sales office to establish the correct selection of units.

## FEATURES

**Refrigerant R410A.** Each complete system uses refrigerant R410A which is deemed to have zero ozone depletion potential.

**Efficient.** The outdoor unit incorporates a high efficiency scroll compressor. Heat exchange coils incorporate inner grooved (rifled) tube for better heat transfer.

**Performance.** A dynamically balanced forward curved fan with a multi-speed motor enables fine tuning of the indoor unit to match the supply air requirements. The system includes a temperature sensing head pressure control which enables the system to compensate for outdoor ambient temperatures below 20°C on cooling cycle, and above 15°C on heating cycle.

**Quiet.** The compressor is isolated in a built-in, insulated compartment to minimise noise. The indoor unit is also insulated for noise attenuation.

**Slimline.** The compact up-right design of the outdoor unit requires only a 150 mm gap on the coil side where installation is against a wall. Its vertical discharge fans are particularly practical where there is restricted space, e.g. beside narrow pathways, or garden plants nearby.

**Durable.** The outdoor coil fins are epoxy coated for extra protection in corrosive environments, e.g. salt laden sea air. The outdoor unit's cabinet is constructed from high grade galvanised steel - polyester powder coated (grey) for all weather protection (IP 45). External fasteners are stainless steel. Heat exchange coils comprise aluminium plate fins on mechanically expanded rifled copper tube. The indoor unit's cabinet is constructed from high grade galvanised steel and also includes a plastic drain tray for complete corrosion resistance.

**Service Access.** The indoor unit's built-in drain tray can be removed for ease of cleaning and service accessibility.

**Insulation.** Closed cell foam insulation has been used in the indoor unit's cabinet to ensure no particles are introduced into the air stream. The insulation is foil faced and meets fire test standards AS 1530.3 (1989) and BS 476 parts 6 & 7.

**Mounting.** The indoor unit can be mounted rigid, or using the optional spring mounting brackets which minimise transfer of vibration.

**Self Diagnostics.** The Outdoor Unit Controller (OUC) has a display of LEDs to indicate faults and running conditions. A non-specific fault indicator is included for interface to external systems.

## OPTIONAL EQUIPMENT

Outdoor Unit:

1. Anti-vibration mounts (rubber)
2. Drain connection - right angle
3. Soft Starter.

Indoor Unit:

1. Filter box - integrated return air spigot and washable polypropylene net filter.
2. **temperzone** SAT Controller.
3. Spring Mounting Kit.
4. 4.5 kW electric booster heater box - complete with safety cutouts required to meet AS/NZS 3350.2.40 1997.
5. Supply and return air plenums.
6. Safety drain tray.

## SAFETY FEATURES

1. HP and loss of refrigerant protection.
2. Anti-rapid cycle timer and internal overload for compressor protection.
3. Circuit breaker control circuits.
4. Time-and-temperature controlled electronic de-ice switch prevents icing up of the outdoor coil during heating cycle.
5. Frost protection on cooling cycle.
6. Sensor fault indication.
7. Compressor minimum run time to ensure oil return.

## COMPRESSOR

Each high efficiency scroll type compressor is hermetically sealed, quiet running and supported on rubber mounts to minimise vibration.

## REFRIGERATION PIPING

The standard unit contains allows for a line length up to 30 m. For line lengths between 30 m and 40 m, refer to **temperzone's Split Systems Installation Guide** (refer [www.temperzone.biz/Technical Support](http://www.temperzone.biz/Technical Support)).

Maximum line length when extended is 60m.

Max. height separations between units are :  
 Outdoor unit above indoor unit : 20 m  
 Outdoor unit below indoor unit : 20 m.

The OSA 155 is shipped from the factory with a charge of HFC-410A (R410A) refrigerant sufficient for a 10 m line length. Liquid and suction service valves are provided. Accurator expansion devices control the flow of refrigerant. The matched indoor unit is shipped with a holding charge of nitrogen. Both units have brazed pipe connections.

## WIRING

The electrical supply required (including voltage fluctuation limits) is:  
**OSA 155RKSV:** 1 ph. 200-252 V a.c. 50 Hz, a start assist facility is included;  
**OSA 155RKTV:** 3 ph. 342-436 V a.c. 50 Hz, with neutral and earth.


The compressor crankcase heater requires a 24 hour power supply. A control panel, located in the outdoor unit, is fully wired ready to accept the main power supply.

The manufacturer operates a quality management system that conforms to AS/NZS ISO 9001:2008.

## AIR HANDLING

**Note:** Airflows are for a dry coil. Reduce airflow by 5% in high moisture removal conditions. In a free blow application, beware of exceeding indoor fan motor's full load amp limit.

As filters are optional, the fan air flows given are for units installed without filters.



## ELECTRICAL

	OSA:	RKS	RKT
E.E.R. (cooling)		2.75	2.75
Indoor Fan Full Load Amps		4.4	4.4
Running Amps (Total System)		25	11 / 8 / 7
Recommended External Fuse		45 A	25 A

## PERFORMANCE DATA

### COOLING CAPACITY (kW)

Total = Total Capacity (kW)      Sens. = Sensible Capacity (kW)  
 E.A.T. = Entering Air Temperature      ○ = Nominal Capacity (kW)

**Note:** Capacities are **gross** and do not include allowance for fan motor heat loss. Capacities are for close coupled systems. Interconnecting pipework will reduce capacity.

MODELS Indoor / Outdoor Unit	INDOOR FAN		INDOOR COIL E.A.T.		OUTDOOR COIL ENTERING AIR TEMPERATURE °C D.B.											
	SPEED	AIR l/s	W.B. °C	D.B. °C	23		27		31		35		39		43	
					Total	Sens.	Total	Sens.	Total	Sens.	Total	Sens.	Total	Sens.	Total	Sens.
ISD 155K / OSA 155RK	HIGH	800	15	21	14.3	11.3	14.1	11.3	13.7	11.1	13.0	10.7	12.2	10.1	11.1	9.3
			17	23	15.0	11.0	14.8	11.0	14.4	10.8	13.8	10.5	12.9	10.0	11.9	9.2
			19	27	15.8	12.6	15.6	12.6	15.2	12.4	14.5	12.1	13.7	11.5	12.6	10.7
			21	31	16.5	14.9	16.3	15.0	15.9	14.8	15.3	14.3	14.4	13.7	13.4	12.8

#### Indoor Air Flow Correction Factors @ nominal conditions

	Indoor Air Flow (%)			
	-20%	-10%	Rated	+10%
Total Capacity	0.95	0.975	1.0	1.025
Sensible Capacity	0.89	0.950	1.0	1.050

### PIPE LENGTH CAPACITY LOSS

ON COOLING CYCLE DUE TO PRESSURE DROP

**Note:** Loss percentage is approximate only.  
 No allowance made for vertical piping.

Pipe Size (mm)		Equivalent Line Pipe Length (m)					Additional Pipe Length to allow per Bend	
Liquid	Suction	5	10	15	20	30	Suction Pipe Size OD	22 mm
13	22	0.7 %	2.1 %	3.4 %	4.7 %	6.1 %	Long 90° Radius (2 x pipe dia.)	0.5 m

### HEATING CAPACITY (kW)

G = Gross Heating Capacity kW, based on nominal air flow of 800 l/s.  
 N = Net Heating Capacity kW allowing for average defrost.

○ = Nominal Capacity (kW)

MODELS Indoor / Outdoor Unit	INDOOR ENTERING AIR TEMP. °C D.B.	OUTDOOR COIL ENTERING AIR TEMPERATURE (E.A.T.) °C D.B.															
		-5		-3		-1		1		3		5		7		9	
		G	N	G	N	G	N	G	N	G	N	G	N	G	N	G	N
ISD 155K / OSA 155RK	15	9.6	8.6	10.4	9.3	11.1	9.9	11.8	10.1	12.5	10.7	13.4	12.8	14.3	14.3	15.0	15.0
	20	9.4	8.4	10.2	9.1	10.9	9.7	11.6	9.9	12.3	10.5	13.2	12.5	14.0	14.0	14.7	14.7
	25	9.0	8.1	9.8	8.8	10.5	9.3	11.1	9.6	11.8	10.1	12.7	11.9	13.5	13.5	14.2	14.2

### SOUND LEVELS

#### Sound Power Levels (SWL)

**Test Conditions:** BS 848 PT2 1985. Installation Type A (free inlet and outlet). Direct method of measurement (reverberant room).  
 Measured in decibels re 1 picowatt.

#### Indoor Unit - Supply Air Outlet

FAN SPEED	AIR FLOW l/s	SWL dB(A)	OCTAVE BAND FREQUENCY Hz					
			125	250	500	1 k	2 k	4 k
			SOUND POWER LEVELS (SWL) dB					
LOW	530	66	58	58	59	57	54	51
MED/LOW	610	65	61	61	61	60	57	54
MED	680	68	65	66	65	64	61	58
HIGH	800	72	69	71	67	68	65	63

#### Outdoor Unit

MODEL	FAN SPEED	SWL dB(A)	OCTAVE BAND FREQ. Hz						SPL @ 3 m dB(A)	OCTAVE BAND FREQ. Hz					
			125	250	500	1 k	2 k	4 k		125	250	500	1 k	2 k	4 k
			SOUND POWER LEVELS dB							SOUND PRESSURE LEVELS dB					
OSA 155	LOW	68	75	68	64	64	54	47	52	59	52	48	48	38	31
	MED	69	78	71	67	64	57	51	53	62	55	53	48	41	35





Sound Pressure Level (SPL) in decibels re 20 µPa.

## DIMENSIONS (mm)

Not to Scale


### ISD 155K Indoor Unit

Net Weight 46 kg  
Shipping Weight 48 kg




### OSA 155RKV Outdoor Unit

Net Weight 136 kg  
Shipping Weight 157 kg




### Recommended Pipe Line Sizes

Liquid: 13 mm OD  
Suction: 22 mm OD



### Note

Materials and specifications are subject to change without notice due to the manufacturer's ongoing research and development programme.



### temperzone limited

Head Office, Auckland : 38 Tidal Rd, Mangere, N.Z.  
Private Bag 93303, Otahuhu, NEW ZEALAND.  
Email sales@temperzone.co.nz Website: www.temperzone.biz

### temperzone australia Pty Ltd

Head Office, Sydney : 7A Bessemer St  
PO Box 6448, Delivery Centre, Blacktown, NSW 2148,  
AUSTRALIA. Email sales@temperzone.com.au

#### AUCKLAND

Ph. 0-9-279 5250  
Fax 0-9-275 5637

#### WELLINGTON

Ph. 0-4-569 3262  
Fax 0-4-566 6249

#### CHRISTCHURCH

Ph. 0-3-379 3216  
Fax 0-3-379 5956

#### SYDNEY

Ph. (02) 8822-5700  
Fax (02) 8822-5711

#### ADELAIDE

Ph. (08) 8376-1505  
Fax (08) 8376-1449

#### SINGAPORE

Ph. SNG 6733 4292  
Fax SNG 6235 7180

#### MELBOURNE

Ph. (03) 8769-7600  
Fax (03) 8769-7601

#### BRISBANE

Ph. (07) 3308-8333  
Fax (07) 3308-8330

#### NEWCASTLE

Ph. (02) 4962-1155  
Fax (02) 4961-5101



#### PERTH

Ph. (08) 9314-3844  
Fax (08) 9314-3855

#### TOWNSVILLE

Ph. (07) 4773-9566  
Fax (07) 4773-9166

#### HOBART

Ph. (03) 6272-0066  
Fax (03) 6272-0506

Available from